

WALK THROUGH METAL DETECTOR

GRD-UC 700 18 zones standard

PARAMETERS:

- Power Supply: AC85V-264V
- Working temperature :-20°C--+50°C
- Working Frequency: 4KHZ—8KHZ
- Standard External size: 2230mm(H)X830mm(W)X730mm(D)
- Standard Internal size: 2000mm(H)X700mm(W)X605mm(D)
- Package size for door panels: 2260*635*235mm *1ctn
- Package size for control unit: 740*320*205m*1ctn
- Gross weight: 75KG

CHARACTERISTIC & FUNCTION:

18 detecting zones, Simultaneous alarm from multi-zones;

Sensitivity adjustable: Each zone has 255 sensitivity level

Small LCD screen, English operating software, easy to operate.

Using high density fireproof material

LED alarm: Two Sides LED indicator, easily show where the metal is.

Automatically count passengers and alarm times

Password protection, only the authorized person can operate.

Easy assembly: designed with only 2 pieces cables and 8 screws, Simply-to-follow instruction. Anti-interference function, using advanced interactive transmitting and receiving to avoid interference.

Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc.

Modularization design, easy for maintenance and replacement.

Sensitivity Test piece: One Metal Coin, omnidirectional detection

4-8 hours backup battery (Option)

4-8 hours backup battery (Option) Waterproof can be used outside

Application

Airport, railway /subway stations, Banks, Embassies, Entertainment environments, Gymnasiums,



T: 0212.2258050 pbx M: bilmak@bilmak.com.tr www.bilmak.com.tr











Guardex